


Wireless Temperature Sensor

Lug-mounted for on-metal applications



RFM3260

APPLICATIONS

Switchgear monitoring
Electric busbar monitoring
Factory power mains
Data center power
Ring-main-units

KEY FEATURES

Normal temperature range
-40 °C to +85 °C

High-temperature alarm
up to +125 °C

Powered by Magnus® S3

Sensor size
52 x 26 x 27 mm

Battery-free design

Secure lug-mounting

Battery-free equipment monitoring

The RFM3260 is a wireless battery-free temperature sensor. This lug-mounted sensor is designed to monitor electric distribution and switching equipment temperatures. Typical applications include utility-grade electric power distribution, factory and industrial electric service switchgear, large office building power distribution, data centers, remotely distributed ring-main-unit (RMU) attachments to the primary electric grid, and other applications where metal surfaces are common.

Wireless temperature sensing

The RFM3260 has a normal operating temperature range of -40 °C to +85 °C. This covers the typical operating temperatures of most equipment over a range of environmental operating conditions. The RFM3260 reports temperatures beyond its normal operating range to as high as +125 °C, although prolonged operation at such an elevated temperature is not recommended.

Rugged design for use on metal and equipment

The RFM3260 incorporates a unique antenna design for harsh environments subject to temperature extremes. The integrated RF antenna harvests energy for the temperature sensing function, as well as communicates with a RAIN/UHF compliant reader. The integrated antenna is suitable for use on metal surfaces that might otherwise adversely affect wireless/RF communication range.

Compliance




The RFM3260 is available in FCC and EU/ETSI frequency ranges. The RFM3260 requires a RAIN/UHF compliant reader. These sensors can be purchased separately or as part of a system.



RFM3260 Performance Data

Rugged temperature sensor for on-metal and industrial applications

PARAMETER	VALUE
Normal temperature range	-40 °C to +85 °C
High-temperature alarm	Up to +125 °C
Compatible standards	EPC class 1 gen 2 v2.0.1 ISO 18000-6C
Integrated circuit	Powered by Magnus® S3
TID memory	64-bits
EPC memory	160-bits supporting up to 128-bit EPC
EPC programming code	Pre-programmed with a 4-character ASCII code
User memory	128-bits
Sensor Size	52 x 26 x 27 mm
Thermal backing plate	Zinc-coated copper
Mounting	Lug tab with opening for 14mm diameter bolt
Shipment method	Cardboard box with foam spacer
Minimum order quantity	5 pc MOQ
Ordering information	RFM3260-AFS (FCC 902 to 928 MHz) RFM3260-AES (ETSI 865.6 MHz to 867.6MHz)



©2017 RFMicron, Inc. All rights reserved. Reproduction in part or in whole is prohibited without prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice. RFMicron, and RFMicron, Inc. as well as the product and service names mentioned herein are the registered trademarks of RFMicron, Inc. All other trademarks are the property of their respective owners. RFMicron, Austin Texas, USA.